















## System overview

### Profile rails DIN35



DIN rail DIN35, universal carrier made of a sheet metal profile in electrical engineering for fastening electrical equipment in distribution boxes, control cabinets, junction boxes, etc. Different components (e.g. relays, impulse switches, timers, circuit breakers, terminal blocks) can be slid onto a carrier rail from the side or plugged in and locked from the front. This standardized method facilitates the assembly of control cabinets and switch boxes, thus reducing labor costs. The different types of rails are in the standard EN 60715.

## Components

	<b>3401 - Mounting rail DIN35 2000mm 35x7.5x1mm</b> DIN35 rail with 35x7.5x1mm, made of galvanized steel, with a 16 mm <sup>2</sup> copper cross section, unperforated, with Woertz lettering every 150 mm according to EN 60715 TH, 2 m length.	
	<b>3401IN - Mounting rail DIN35 made of VA4 steel 2 m</b> DIN35 rail with 35x7.5x1 mm, made of VA4 steel, with a 16 mm <sup>2</sup> copper cross-section, 2 m long.	
	<b>3490/L - Mounting rail DIN35 2000mm 35x15x2.5mm</b> Mounting rail DIN35 with 35x15x2.5 mm, made of galvanized steel, with a 50 mm <sup>2</sup> copper cross-section according to EN 60715, with longitudinal hole, 2 m length.	
	<b>80290 - DIN35 copper mounting rail 2 m</b> DIN35 rail with 35x15x2.3 mm, made of copper, with a 6 mm <sup>2</sup> copper cross section, 2 m length.	
	<b>3401/L - DIN35 steel galvanized mounting rail 2 m</b> DIN35 mounting rail with 35x7.5x1 mm, made of galvanized steel, with a 16 mm <sup>2</sup> copper cross-section, with mounting slots as well as Woertz lettering every 150 mm according to EN 60715 TH, with longitudinal hole, 2 m length.	
	<b>3400A - Combination rail DIN35/DIN15 of aluminum 2 m</b> Combination rail Extrudal-050 DIN35/DIN15, with 35x7.5x3.3 mm, made of aluminum alloy, with a 35 mm <sup>2</sup> copper cross-section, 2 m length	





System overview

Profile rails DIN35



**80291/6M - Combination rail DIN35/C30 of aluminum 6 m**

Combination rail Extrudal-050 DIN35/C30 with 35x15x1 mm made of aluminum alloy, with a 85 mm<sup>2</sup> copper cross section, 6 m length.



**80291/3M - Combination rail DIN35/C30 of aluminum 3 m**

Combination rail Extrudal-050 DIN35/C30 with 35x15x1 mm made of aluminum alloy, with a 85 mm<sup>2</sup> copper cross section, 3 m length.



**80291/2M - Combination rail DIN35/C30 of aluminum 2 m**

Combination rail Extrudal-050 DIN35/C30, with 35x15x1 mm made of aluminum alloy, with a 85 mm<sup>2</sup> copper cross-section, 2 m length.

