

















System overview

Shielding terminals type C30 made of hardened aluminum alloy



- With pin and with spring
- Profile rails No. 4382,4383 and 80291, type C30 serves as busbar
- Remove cable sheath, expose shield
- Handle like quick installer
- With steel spring that creates contact without damaging shield
- Do not use as a cable fastener!








Components

	<b>43711 - Shielding terminal C30 6-10mm</b> made of aluminum alloy, hardened	
	<b>43712 - Shielding terminal C30 8.5-12.5mm</b> made of aluminum alloy, hardened	
	<b>43713 - Shielding terminal C30 11.5-15.5mm</b> of hardened aluminium alloy	
	<b>43714 - Shielding terminal C30 14-5-19.5mm</b> of hardened aluminium alloy	
	<b>43715 - Shielding terminal C30 18-26mm</b> of hardened aluminium alloy	
	<b>43716 - Shielding terminal C30 25-33mm</b> of hardened aluminium alloy	
	<b>4382IN/3M - Profile rail C30 stainless steel V2A 3 m</b> Profile rail C30 with 29x15x2 mm made of stainless steel V2A, with a length of 3 m.	



System overview

Shielding terminals type C30 made of hardened aluminum alloy

	<p><b>4383IN/3M - Profile rail C30 stainless steel V2A 3 m</b></p> <p>Profile rail C30 with 32x18x3 mm made of stainless steel V2A, with a length of 3 m.</p>	
	<p><b>80170/16 - Bare earthing terminal 16mm2</b></p> <p>with anchoring stud for mounting rail C30</p>	
	<p><b>80170/50 - Bare earthing terminal 50mm2</b></p> <p>with anchoring stud for mounting rail C30</p>	
	<p><b>80291/2M - Combination rail DIN35/C30 of aluminum 2 m</b></p> <p>Combination rail Extrudal-050 DIN35/C30, with 35x15x1 mm made of aluminum alloy, with a 85 mm<sup>2</sup> copper cross-section, 2 m length.</p>	