





| Characteristics                           |                     |
|---|---------------------|
| Eldas number                              | 158210257           |
| Base Unit                                 | Piece               |
| availability                              | Delivery in 4 weeks |
| EAN Code                                  | 7611718202162       |
| group                                     | 165000              |
| Packaging unit                            | 50                  |
| country of origin                         | СН                  |
| Customs tariff number                     | 8536.9080           |
| Weight (g)                                | 12,8 g              |
| Color                                     | blue                |
| Technical data                            |                     |
| Dimensions length x width x height (mm)   | 49x6x44 mm          |
| Dimensions length x width x height (inch) | 1.93x0.24x1.73 inch |
| Cross section (mm²)                       | 0,5 - 4 mm²         |
| Nominal current (A)                       | 32 A                |





| Rated voltage (V)                       | 1000 V         |
|---|----------------|
| Connection type                         | Screw terminal |
| DIN rail type                           | DIN-32         |
| Number of connection point              | 2              |
| Number of floor                         | 1              |
| Number of potentials                    | 1              |
| Clamping screw M                        | МЗ             |
| Insulating material                     | PA66           |
| Nominal Cross-section (mm²)             | 4 mm²          |
| Stripping length mm (mm)                | 10 mm          |
| Head reception room width x height (mm) | 3.4x6 mm       |
| Rating data according to UL 1059        |                |
| Rated voltage US (V)                    | 600 V          |
| Nominal cross section (AWG)             | 12 AWG         |
| Cross-section (AWG)                     | 12 - 20 AWG    |
| Stripping length (inch)                 | 0,39 inch      |
|   |                |





### 3301BL - Terminal DIN32 4mm2 blue

#### **Product accessories**

| 8  | 30070R - Test plug Ø M3 red, socket 4mm                     |
|--|---|
| p  | olug and adaptor in one piece                               |
|  |   |
| 8  | 30070S - Test plug Ø M3 black, socket 4mm                   |
| р  | olug and adaptor in one piece                               |
| 2  | 2737R - Test plug Ø 2.8mm red, socket 4mm                   |
| and the second s |   |
|  | connecting cable incl.                                      |
| 2  | 2737S - Test plug Ø 2.8mm black, socket 4mm                 |
| C  | connecting cable incl.                                      |
|  |   |
| \$   | Bezeichnungskarte_6x12mm - Designation cards 6x12mm         |
| (*************************************   | /arious designation labels 6x12mm with different embossing. |
|  |   |
|  | Bezeichnungskarte_6x9mm - Designation card 6x9mm            |
| V  | /arious designation plates with different embossing.        |
| Б  | Bezeichnungskarte_6x3mm - Designation card 6x3mm            |
|  | /arious designation plates with different embossing.        |
|  |   |
| 3  | 661GR - End barrier DIN32 grey to 3301                      |
| n  | null  |
| 3  | 8651GR - Partition DIN32 grey to 30111,3301,3302            |
|  | or 30111,3301,3302  |
|  | 013011,3301,3302  |
| 3  | 3758 - Stopper DIN32 height 30mm                            |
| ALC:   | rom polyamide gray  |
| 3  | 8749 - Stopper DIN32 height 28mm                            |
| - 5-   | of anticorodal  |
|  |   |





| Ħ        | 81506/2 - Cross-connection 2-pole to terminals DIN32/35 4mm² Insulated cross-connection 2-pole to terminals DIN32/35 4mm² including screws M3. Standard version. Dimension: 11.1x20.8 mm                             |
|----------|--|
|          | 81506/3 - Cross-connection 3-pole to terminals DIN32/35 4mm² Insulated cross-connection 3-pole to terminals DIN32/35 4mm² including screws M3. Standard version. Dimension: 17.2x20.8 mm                             |
|          | 81506/4 - Cross-connection 4-pole to terminals DIN32/35 4mm² Insulated cross-connection 4-pole to terminals DIN32/35 4mm² including screws M3. Standard version. Dimension: 23.3x20.8 mm                             |
|          | 81506/5 - Cross-connection 5-pole to terminals DIN32/35 4mm² Insulated cross-connection 5-pole to terminals DIN32/35 4mm² including screws M3. Standard version. Dimension: 29.4x20.8 mm                             |
|          | 81506/10 - Cross-connection 10-pole to terminals DIN32/35 4mm <sup>2</sup> Insulated cross-connections 10-pole to terminals DIN32/35 4mm <sup>2</sup> including M3 screws. Standard version. Dimension: 59.9x20.8 mm |
|          | 81506 - Cross connection bolt single M3 insulated (10.6 mm)  Cross-connection bolt complete with spacer sleeve. Standard version. Dimension: 10.6 mm   |
|          | 81410L - Link to cross-connections  Connecting lug to terminals 4mm². Dimension: 11.1x8 mm   |
|          | 80049/4 - Warning plate for single terminal 4mm2 to series 3450  |
| Woertz © | 3886/4 - Cover for 4 terminals yellow with black printing, to series 3424,3450   |
| Woertz © | 3886/5 - Cover for 5 terminals yellow with black printing, to series 3424,3450   |
| A Margan | 3886/6 - Cover for 6 terminals yellow with black printing, to series 3424,3450   |





| - D  | 3886/7 - Cover for 7 terminals yellow with black printing, to series 3424,3450   |
|--|--|
|  | 3886/8 - Cover for 8 terminals yellow with black printing, to series 3424,3450   |
|  | 81440 - Sealing eyelet Ø 3.2mm Sealing eyes  |
| Sur.   | 3512 - Sealing screw M3x25 of polyamide  Sealing screw spring-loaded test probes, several numbers of poles can be lined up |
| and the state of t | 30422 - Cover strip for terminal blocks 9.5mm, length 280mm  Cover strip for terminal blocks DIN32/35 9.5mm, length 280mm  |





3301BL - Terminal DIN32 4mm2 blue

# **Product systems**



#### Terminal blocks DIN32 2.5mm<sup>2</sup>-70mm<sup>2</sup>

Various terminal blocks DIN32 2.5mm<sup>2</sup>-70mm<sup>2</sup>.

