



49845WS - Flat cable power 5G2.5 mm<sup>2</sup> PVC WS



Flat cable Woertz power 5x2.5 mm², PVC white 3LNPE

| Characteristics                 |                                 |
|---------------------------------|---------------------------------|
| Eldas number                    | 113383834                       |
| Base Unit                       | Meter                           |
| availability                    | Delivery according to agreement |
| EAN Code                        | 7611718257605                   |
| group                           | 170000                          |
| Packaging unit                  | -                               |
| country of origin               | СН                              |
| Customs tariff number           | 8544.4992                       |
| Weight (g)                      | 259 g                           |
| Copper weight (g)               | 120 g                           |
| Technical data                  |                                 |
| Construction (mm <sup>2</sup> ) | 5x2.5 mm²                       |
| Dimensions width x height (mm)  | 24x6 mm                         |
| Halogen free                    | No                              |
| Cable type                      | PVC flat cable                  |





### 49845WS - Flat cable power 5G2.5 mm<sup>2</sup> PVC WS

| International designation          | N1VVH2-K                           |
|------------------------------------|------------------------------------|
| Reaction to fire classification    | Eca                                |
| Cross section (mm <sup>2</sup> )   | 2.5 mm <sup>2</sup>                |
| Copper conductor                   | Tinned, flexible KL5 EN60228       |
| Conductor resistance (ohm/km)      | 8,21 ohm/km                        |
| cores insulation                   | PVC                                |
| Cores colors                       | gray,black,brown,blue,green/yellow |
| Sheat insulation                   | PVC                                |
| Sheath color                       | Black                              |
| Minimum bending radius             | 6xH                                |
| Operating Temperature (°C)         | -25 to 70 °C                       |
| Installation temperature min. (°C) | 5 °C                               |
| Nominal voltage (VAC)              | 600/1000 VAC                       |
| Test voltage                       | 4 kV/50Hz                          |
| Fire load (kWh/m)                  | 0,778                              |
| Flame retardant according to       | IEC/EN60332-1-2                    |





49845WS - Flat cable power 5G2.5 mm² PVC WS

### **Product accessories**

| -  | 9054 - Cable clamp 13.5 mm to flat cable Technofil  |
|--|---|
| C  | Cable clamp 13.5 mm to flat cable Technofil to screw on   |
|  | 49731 - Fastening clamp FC combi / power  |
|  | to screw on   |
|  | 49733 - Fastening clamp FC combi / power  |
| A CONTRACTOR OF THE OWNER OWNER OF THE OWNER OWNE OWNER OWNE | Cable clamp screw-on, for flat cable power 5G2.5 mm <sup>2</sup>  |
|  | 49960 - Insulating pad for flat cable   |
|  | Scotch 2210   |
|  | 49733A - Fastening clamp FC combi / power Glue  |
| A CONTRACTOR OF THE OWNER OWNER OF THE OWNER OF THE OWNER OWNE   | Cable clamp for gluing, for flat cable power 5G2.5 mm <sup>2</sup>  |
| Cabl   | 48510/05 - End piece Technofil / Power/Dali 3P IP68   |
|  | Cable end piece IP68 for flat cable Technofil 5G2.5 mm <sup>2</sup> , Power 5G2.5 mm <sup>2</sup> and DALI 3G2.5 mm <sup>2</sup> 2x1.5 mm <sup>2</sup> .  |
| N<br>W<br>W<br>2   | 49386 E90 - Riser clamp E90   |
|  | Max. Bride load: 50kg. For Woertz fire safety flat cable: Woertz FE180 3G2.5 and 4 mm <sup>2</sup> ,<br>Woertz FE180 5G2.5, 4 6 mm <sup>2</sup> . For Woertz flat cable: Woertz Technofil 5G2.5 1.5 mm <sup>2</sup> ,<br>Woertz power 5G2.5 mm <sup>2</sup> , Woertz Power IP 5G2.5 mm <sup>2</sup> 6 mm <sup>2</sup> , Woertz combi 5G2.5 mm <sup>2</sup><br>2x1.5 mm <sup>2</sup> , Woertz Dali IP 5G2.5 mm <sup>2</sup> 2x1.5 mm <sup>2</sup> , Woertz Dali 3/5G2.5 mm <sup>2</sup> 2x1.5 mm <sup>2</sup> ,<br>Woertz 5G4 mm <sup>2</sup> , Woertz 7G2.5 mm <sup>2</sup> . |



#### 49935 - Cutting shears up to 6 mm<sup>2</sup>

Woertz flat cable shears up to 5x6 mm<sup>2</sup> (with higher force up to 5x16 mm<sup>2</sup>)





49845WS - Flat cable power 5G2.5 mm<sup>2</sup> PVC WS

### Product systems

