



Product data sheet

48957 - Endbox FC E90 5G16 with cap IP68



| Characteristics | |
|---|---------------------------------|
| Base Unit | Piece |
| availability | Delivery according to agreement |
| group | 170000 |
| Packaging unit | 1 |
| country of origin | CH |
| Customs tariff number | 8536.9080 |
| Technical data | |
| Fire load (KWh) | 2,4 kWh |
| Dimensions length x width x height (mm) | 35x43.7x30.7 mm |
| Dimensions length x width x height (inch) | 1.37x1.72x1.21 inch |
| Degree of protection | IP66/IP68 (2m,30min) |
| Metal parts | Corrosion protected |
| Number of poles | 5 pole |
| Contacting type | Screw terminal |
| Connection conductor (mm²) | 5x16 mm² |



Product data sheet

48957 - Endbox FC E90 5G16 with cap IP68

| | |
|---|-----------------------|
| Connecting capacity (mm) | 6.3 mm |
| Rated current heavy current part (A) | 76(16mm2) A |
| Operating Temperature (°C) | -15 to 85 °C |
| Installation temperature min. (°C) | 5 °C |
| Function maintenance | E30/E90 (DIN 4102-12) |
| Plastic parts | Halogen-free |
| Material housing | Ceramics |
| Number Screwdriver Clamping screws Heavy current part | schraubklemmen |



Product data sheet

48957 - Endbox FC E90 5G16 with cap IP68

Product accessories



Product data sheet

48957 - Endbox FC E90 5G16 with cap IP68

Product systems



FE180 E30/E90 5G16 mm²

Woertz fire safety system FE180 E30/E90 5G16 mm² for power supply of safety-relevant elements, such as emergency and escape route lighting, smoke extraction systems or fire department elevators.

