



Floor channel BOK 8880 200x50mm on leveling device



Floor channel BOK 8880 200x50mm on leveling device.

Components

	55032 - Installation kit Sts 4FLF horizontal empty BOK	
	made of galvanized sheet steel 1.5mm with knurled screw for lateral fixing in the trunking shell. Dimension: 376x47(53)x40mm Color: RAL 7032 pebble gray Equipped: 1 pcs. blind hole clamp 8x2.5mm ² 10146	
	52515 - Leveling foot M10 cpl H=53mm BOK 8880	
	for finished floor heights:	
	Channel height 50mm, 70-90mm	
	Channel height 60mm, 80-100mm	
	Channel height 80mm, 100-140mm	
1	52516 - Leveling foot M10 cpl H=103mm BOK 8880	
	for finished floor heights:	
	Channel height 50mm, 80-140mm	
	Channel height 60mm, 90-150mm	
	Channel height 80mm, 110-170mm	
4	52517 - Leveling foot M10 cpl H=153mm BOK 8880	
<u></u>	for finished floor heights:	
	Channel height 50mm, 80-190mm	
	Channel height 60mm, 90-200mm	
	Channel height 80mm, 110-220mm	
	52267 - St lid BOK 8880/200 SK BL	



52253 - Angle connection BOK 8880/200x50 SK

brush strips as cable outlet, for 3mm finished floor height

made of sendzimir-galvanized sheet steel 1.5mm pressed into special aluminum profile Woertz on both sides with temporary protective edge inserted into groove and impact sound trapezoidal rubber as cover support including fastening straps and connecting material height 50mm / nominal cover width 200mm

made of sendzimir-galvanized steel sheet 4mm dimension: 500x200mm with







Floor channel BOK 8880 200x50mm on leveling device



52254 - T-joint BOK 8880/200x50 SK

made of sendzimir-galvanized sheet steel 1.5mm pressed into special aluminum profile Woertz on both sides with temporary protective edge inserted into groove and impact sound trapezoidal rubber as cover supportincluding fastening straps and connecting material height 50mm / nominal cover width 200mm length: 1000mm





52255 - Cross connection BOK 8880/200x50 SK

made of sendzimir-galvanized sheet steel 1.5mm pressed into special aluminum profile Woertz on both sides with temporary protective edge inserted into groove and impact sound trapezoidal rubber as cover supportincluding fastening straps and connecting material height 50mm / nominal cover width 200mm length: 1000mm





52250 - Floor duct BOK 8880/200x50 SK

made of sendzimir-galvanized steel sheet 1.5mm pressed into special aluminum profile Woertz on both sides with temporary protective edge inserted into groove and impact sound trapezoidal rubber as cover support including fastening straps and connecting material height 50mm / nominal cover width 200mm length: 2000mm





52256 - End wall BOK 8880/200x50 with temporary protective edge

made of sendzimir-galvanized steel sheet 1.5mm with temporary protective edge pressed into special aluminum profile Woertz with temporary protective edge inserted into groove and impact sound trapezoidal rubber as cover supportincluding connecting material height 50mm / nominal cover width 200mm





51431 - St lid BOK 8880/200 SK

made of steel sheet 4mm dimension: 500x200mm with opening for connection attachment





52265 - St lid BOK 8880/200 SK

made of sendzimir galvanized steel sheet 4mm dimension:1000x200mm





52272/12 - 0

for 12mm edge, to BOK 8880/200, Length: 1000mm





52277 - Temporary wooden cover BOK8880/200

for insertion as a placeholder and protection for the floor channel Dimension: 1000x201x12mm







	52266 - St lid BOK 8880/200 SK KD	
	made of sendzimir-galvanized steel sheet 4mm dimension: 500x200mm cable gland loosely enclosed	
	52268 - St lid BOK 8880/200 SK KMn	
The state of the s	made of sendzimir-galvanized steel sheet 4mm dimension: 500x200mm cable tray enclosed loose	
	52269 - St lid BOK 8880/200 SK	
	made of sendzimir galvanized steel sheet 4mm dimension: 500x200mm	
	52272/3 - 0	
	aluminium 2mm galvanised sheet steel reinforced 3mm getoxt. Dimensions: 1000x199x7mm Edge height in 3mm	
	52273/3 - 0	
	made of aluminum 2mm toxtured with galvanized steel sheet insert 3mm. Dimension: 500x199x7mm edge height inside occupiable: 3mm	
	52272/22 - 0	
	for 22mm edge, to BOK 8880/200,Length: 1000mm	
Ť.	52410/22 - Al protective edge 22 BOK 8880	
51. 85.	made of aluminumDimension: 2000x37x3mm	
	52410/3 - Al protective edge 3 BOK 8880	国第38年3月日 月間20日 1月間20日 1日日 1日日 1日日 1日日 1日日 1日日 1日日 1日日 1日日 1
** **	made of aluminumDimension: 2000x18x3mm	
	52410/12 - Al protective edge 12 BOK 8880	
2 8	made of aluminumDimension: 2000x27x3mm	
<u> </u>	52412/3 - Cr protective edge 3 BOK 8880	
2 8	made of chrome steel V2Adimension: 2000x18x3mm	
3	52412/12 - Cr protective edge 12 BOK 8880	
51 + 36	made of chrome steel V2Adimension: 2000x27x3mm	
-3 -2 -8	52412/22 - Cr protective edge 22 BOK 8880	
	made of chrome steel V2Adimension: 2000x37x3mm	





	55033 - Installation kit Sts 6FLF horizontal empty BOK	
	made of galvanized sheet steel 1.5mm with knurled screw for lateral fixing in the trunking shell. Dimension: 525x47(53)x40mm Color: RAL 7032 pebble gray Equipped: 1 pcs. blind hole clamp 10x2.5mm ² 10128	
	52345 - Installation kit Scs 3FLF horizontal empty BOK	
	Low current version made of sendzimir galvanized sheet steel 1.5mm with strain relief stampings and knurled screw for lateral fixing in the trunking shell Dimension: 400x95x41.4mm Color: RAL 7032 pebble gray	
4	52200 - Leveling bar straight BOK 8880/200	
	made of steel dimension: 330x50x5mm	
	52091 - Mounting bracket 1 FLF 3/5 empty BOK	
	made of galvanized sheet steel color: RAL 7032 pebble gray	
	52267/0 - St lid BOK 8880/200 SK 0 BL	
	made of sendzimir-galvanized steel sheet 4mm dimension: 500x206mm with brush strips as cable outlet, for 3mm finished floor height	
	52269/0 - St lid BOK 8880/200 SK 0	
	made of sendzimir galvanized steel sheet 4mm dimension: 500x206mm	
	51880 - Cable bushing with filler piece BOK	
	made of polycarbonate crystal clearwith transparent fillerDimension: 86x60x9.5mm	
	52502 - Leveling plate BOK 8880/200	
	made of sendzimir galvanized sheet steel dimension: 330x330x4mm to angle- cross- and T-connection	
	52273/12 - 0	
	for 12mm edge, to BOK 8880/200,Length: 500mm	
	52273/22 - 0	
	for 22mm edge, to BOK 8880/200,Length: 500mm	





\wedge	52274/12 - 0	回答: \$10 \$50
	of aluminiumdim 500x200edge 12mm cable trough separately enclosed	
\wedge	52274/3 - 0	
	aluminium 2mm galvanised sheet steel reinforced 3 mm getoxtDimensions: 500x200x7mm Edge height in 3 mm Loose cable trough	
4	55028 - Adapter plate BOK 8880/200x50/60	
	made of sendzimir-galvanized sheet steel 1.5mm for mounting the installation kits in the floor ductincluding fastening material	
	51996 - Installation kit Scs 2FLF horizontal empty BOK	回答: 5 5 1 回 7 5 1 5 7 5 7 5 7 5 7 5 7 5 7 5 7 5 7 5
	Low current versionmade of galvanized steel sheet 1.5mm with strain relief stampings and knurled screw for lateral fixing in the trunking shell. Color: RAL 7032 pebble gray	
<u> </u>	52256/0 - End panel BOK 8880/200x50 SK with protective edge height 0	
	made of sendzimir-galvanized steel sheet 1.5mm with protective edge height 0 in special aluminum profile Woertz pressed in groove and impact sound trapezoidal rubber as cover supportincluding connecting material height 50mm / nominal cover width 200mm	
	51432 - Connection attachment 2x5FLF vertical BOK	
	Top 200x219x80 for 10 FLF sockets standing Color: at choice	
30	55039 - Installation kit socket outlet T13 3FLF horizontal SB BOK	
	Installation kit socket T13 3FLF horizontal SB BOK made of galvanized sheet steel 1.5mm with knurled screw for lateral fixing in the trunking shell. Dimension: 302x47(53)x40mm Color: RAL 7032 pebble gray Equipped, wired and tested: 1 pcs. blind terminal 7x2.5mm ² 10127 3 pcs. socket T13 FLF white 55200 1x L1 / 1x L2 / 1x L3 1 pc. Td-cable 5x1.5mm ² / 1000mm 1 pc. FK junction box technofil 49909 (10A)	
	52267/0SB - St lid visible BOK 8880/200 SK 0 BL	
	made of sendzimir galvanized sheet steel 4mm dimension:500x206mm with brush strip as cable outlet, top flush with lid for visible lid	
	52274/22 - 0	
	of aluminiumdim 500x200edge 22mm cable trough separately enclosed	





Floor channel BOK 8880 200x50mm on leveling device

	52278/0SB - Cr lid visible BOK 8880/200 SK 0	
	made of chrome steel V2A 4mm, brushed dimension: 990x206mm	
	52266/0 - St lid BOK 8880/200 SK 0 KD	
	made of sendzimir galvanized steel sheet 4mm dimension: 500x206mm with cable gland	
	52268/0 - St lid BOK 8880/200 SK 0 KMn	
The state of the s	made of sendzimir-galvanized steel sheet 4mm dimension: 500x206mm with cable trough enclosed loose	
	52279/0SB - Cr lid visible BOK 8880/200 SK 0 BL	回款物件是4回 7000年第二章
	made of chrome steel V2A 4mm, brushed Dimensions: 490x206mm With brush strip 54x30mm as a cable outlet Top flush for visible cover	
	55019 - Installation kit bticino 2x2-3gang empty BOK	
Massac Co.	made of galvanized sheet steel color: RAL 7032 pebble gray	
10	55041 - Installation kit socket T23 3FLF horizontal SB BOK	
	Installation kit socket T23 3FLF horizontal SB BOK made of galvanized sheet steel 1.5mm with knurled screw for lateral fixing in the trunking shell. Dimension: 302x47(53)x40mm Color: RAL 7032 pebble gray Equipped, wired and tested: 1 pcs. blind terminal 7x2.5mm ² 10127 3 pcs. socket T23 FLF white 55210 1x L1 / 1x L2 / 1x L3 1 pc. Td-cable 5x2.5mm ² / 1000mm 1 pc. FK socket SK ecobus power 5x2.5² Pow 5P 49701P (16A)	
1000	52344 - Insert Sts 3FLF horizontal SB BOK	
	made of galvanized sheet steel 1.5mm with knurled screw for lateral fixing in the trunking shell Dimensions: 302x47(53)x40mm Color: RAL 7032 pebble gray	
	equipped, wired and tested: 1 pcs. blind hole terminal 7x2.5mm² 10127 3 pcs. socket T13 FLF white 55200 1x L1 / 1x L2 / 1x L3 1 pcs. Td cable 5x1.5mm² / 1000mm. 1 pc. FK socket SK ecobus power 5x2.5² Pow 5P 49701P (16A)	

55031 - Installation kit Sts 3FLF horizontal empty BOK

Equipped: 1 pcs. blind hole clamp 7x2.5mm ² 10127

made of galvanized sheet steel 1.5mm with knurled screw for lateral fixing in the trunking shell. Dimension: 302x47(53)x40mm Color: RAL 7032 pebble gray







	52401 - Mounting bracket 50 BOK 8880/50 made of sheet steel 2.5mm for floor trunking BOK 8880 height 50mm	
	52407 - Connecting link straight BOK 8880 made of sheet steel dimension: 130x10x2.5mm with 4 pieces hexagonal screws M4x8 for connecting the channel shells	
	52408 - Angle connecting link 90° BOK 8880 made of sheet steel dimension: 67.5/67.5xx10x2.5mm with 4 pcs hexagonal bolts M4x8 for connecting the channel shells	
<u></u>	52519 - Leveling foot M10 cpl H=253mm BOK 8880 for finished floor heights: Channel height 50mm, 230-290mm Channel height 60mm, 240-300mm Channel height 80mm, 260-320mm	
‡	52518 - Leveling foot M10 cpl H=203mm BOK 8880 for finished floor heights: Channel height 50mm, 180-240mm Channel height 60mm, 190-250mm Channel height 80mm, 210-270mm	
•	51049 - Adjustable cable trough BOK 8880 fDsb made of polycarbonate crystal clear for cover visible for mounting with threaded bolt	
	52415 - U-clamp profile reinforced 1-3mm as edge protection profile for sheet thickness up to 3mm	
	51069 - Cable trough levelable BOK SK 0-21mm made of polycarbonate crystal clear for cover visible for mounting with threaded bolt	
*	52420 - Brush strip cpl. BOK 8880 s=6 made of plastic, black dimension: 54x35mm bristles length: 25mm	
•	52421 - Brush strip cpl. BOK 8880 s=4 visible made of plastic, black dimension: 54x37mm bristles length: 30mm	