



3425E - Terminal block DIN35 6mm² 49x8x45mm green-yellow insulated



Terminal block DIN35 6mm² 49x8x45mm green-yellow insulated with best possible contacting, stainless steel screws, 4-digit marking possibility on both sides, recessed for cross-connections

| Characteristics | |
|---|---------------------------------|
| Eldas number | 158120367 |
| Base Unit | Piece |
| availability | Delivery according to agreement |
| EAN Code | 7611718205514 |
| group | 165000 |
| Packaging unit | 50 |
| country of origin | СН |
| Customs tariff number | 8536.9080 |
| Weight (g) | 19 g |
| Color | green/yellow |
| Technical data | |
| Dimensions length x width x height (mm) | 49x8x45 mm |
| Dimensions length x width x height (inch) | 1.93x0.32x1.77 inch |
| Cross section (mm ²) | 0,5 - 6 mm² |
| Nominal current (A) | 41 A |





3425E - Terminal block DIN35 6mm² 49x8x45mm green-yellow insulated

| Rated voltage (V) | 1000 V |
|--|-----------------------|
| Connection type | Screw terminal |
| DIN rail type | DIN-35 |
| Smallest connectable section (mm ²) | 0,5 mm² |
| Number of connection point | 2 |
| Number of floor | 1 |
| Number of potentials | 1 |
| Clamping screw M | M4 (M = 1.5Nm) |
| Central thread M | M3 (M = 0.7Nm) |
| Insulating material | PA66 |
| Nominal Cross-section (mm ²) | 6 mm ² |
| Stripping length mm (mm) | 11 mm |
| conductors of the same cross-section per clamping point EN60947 (mm ²) | 1x6 , 2x4 , 2x2.5 mm² |
| Head reception room width x height (mm) | 4.5x6 mm |
| Rating data according to UL 1059 | |
| Rated voltage US (V) | 600 V |
| Nominal cross section (AWG) | 10 AWG |
| Cross-section (AWG) | 10 - 20 AWG |
| Smallest connectable section (AWG) | 20 AWG |
| Stripping length (inch) | 0,43 inch |
| Tightening torque (Ib-inch) | 13,3 lb-inch |
| | |





3425E - Terminal block DIN35 6mm² 49x8x45mm green-yellow insulated

Product accessories

| | 81548/2 - Cross-connection 2-pole to terminal blocks 6mm ² for high demands |
|----|---|
| Ħ | Insulated cross-connection for high demands 2-pole to terminal blocks 6mm ² including screws M3. Dimension: 15.1x20.8 mm |
| ĦĦ | 81548/3 - Cross-connection 3-pole to DIN35 6mm ² terminal blocks for high demands |
| | Insulated cross-connection for high demands 3-pole to terminal blocks DIN35 6mm ² including screws M3. Dimension: 23.2x20.8 mm |
| | 81548/4 - Cross-connection 4-pole to terminal blocks 6mm ² for high demands |
| | Insulated cross-connection for high demands 4-pole to terminal blocks 6mm ² including screws M3. Dimension: 31.3x20.8 mm |
| | 81548/5 - Cross-connection 5-pole to DIN35 6mm ² terminal blocks for high demands |
| | Insulated cross-connection for high demands 5-pole to DIN35 6mm ² terminal blocks including M3 screws. Dimension: 39.4x20.8 mm |
| | 81548/10 - Cross-connection 10-pole to terminals 6mm ² for high demands |
| | Insulated cross-connection 10-pole to DIN35 6mm ² terminal blocks including M3 screws. Dimension: 79.9x20.8 mm |
| Ŧ | 81548 - Cross connection bolt single M3 insulated for high demands (11,5 mm) |
| 1 | Cross-connection bolt complete with spacer sleeve to terminal blocks for high demands. Dimension: 11.5 mm |
| | 81412L - Link to cross-connections |
| | to terminals 6 und 10mm 2 |
| | Bezeichnungskarte_6x12mm - Designation cards 6x12mm |
| | Various designation labels 6x12mm with different embossing. |
| | Bezeichnungskarte_6x9mm - Designation card 6x9mm |
| | Various designation plates with different embossing. |
| | |
| | Various designation plates with different embessing |





3425E - Terminal block DIN35 6mm² 49x8x45mm green-yellow insulated

| 30792 - Cross-junction rack 10pole grey 8mm to terminals with 6mm pin spacing | | |
|--|---|--|
| | 80070R - Test plug Ø M3 red, socket 4mm plug and adaptor in one piece | |
| | 2737R - Test plug Ø 2.8mm red, socket 4mm connecting cable incl. | |
| | 3516 - End barrier DIN35 grey to 3424, 3425 End wall suitable for 3424, 3425 | |
| (,) | 3506 - Partition DIN35 grey to 30128, 3424 Partition wall suitable for 3424, 3425, 30123, 30124, 30127, 30128, 30130 | |
| | 80255 - Push-in barrier DIN35 to 30128, 3424, to 3425, 30138, 30137, white | |
| aumanna | 30422 - Cover strip for terminal blocks 9.5mm, length 280mm Cover strip for terminal blocks DIN32/35 9.5mm , length 280mm | |
| | 3418 - Stopper DIN35 height 30mm Makrolon locking piece | |
| | 30370 - Stopper DIN35 height 23mm Locking piece made of nickel-plated brass M3 screw | |
| · · · | 30199 - Stopper DIN35 height 50mm Aluminum alloy locking piece | |
| woertz o assus | 3887/4 - Cover for 4 terminals yellow with black printing, to series 3425,345210 | |
| - A | 3887/5 - Cover for 5 terminals yellow with black printing, to series 3425,345210 | |





3425E - Terminal block DIN35 6mm² 49x8x45mm green-yellow insulated

| - D | 3887/6 - Cover for 6 terminals yellow with black printing, to series 3425,345210 |
|---|---|
| - D | 3887/7 - Cover for 7 terminals yellow with black printing, to series 3425,345210 |
| - D | 3887/8 - Cover for 8 terminals yellow with black printing, to series 3425,345210 |
| Ļ | 81440 - Sealing eyelet Ø 3.2mm Sealing eyes |
| - And - I and | 3512 - Sealing screw M3x25 of polyamide Sealing screw spring-loaded test probes, several numbers of poles can be lined up |





3425E - Terminal block DIN35 6mm² 49x8x45mm green-yellow insulated

Product systems



Terminal blocks for high demands DIN35

Terminal blocks for high demands DIN35 with best possible contacting, stainless steel screws, 4-digit marking possibility on both sides, recessed for cross connections

