



48100/L2/3C1/S - Quick connect box FC Power 5G2.5 branching 3 pole, code 1 (L2)



Quick connect branching box IP20/IP40 with socket 3 pole code1, L2-N-PE, 250V 20A, for flat cable no.49845 and 49846

Characteristics	
Eldas number	150700207
Base Unit	Piece
availability	available from stock
EAN Code	7611718278839
group	170000
Packing	5
country of origin	СН
Customs tariff number	8536.9080
Weight (g)	190 g
Color	purple
Coding plug connection	Code 1
Technical data	
Вох Туре	Junction boxes
Dimensions length x width x height (mm)	113x61x36 mm
Degree of protection	IP20, IP40 (Connected)





48100/L2/3C1/S - Quick connect box FC Power 5G2.5 branching 3 pole, code 1 (L2)

Flat cable contacting type	Piercing-Kontaktierung (Messer)
Number of poles	3 pole
Rated current heavy current part (A)	20 A
Rated voltage heavy current part (V)	250 V
Operating Temperature (°C)	-15 bis 85 °C
Installation temperature min. (°C)	5 °C
Plastic parts	halogenfrei





48100/L2/3C1/S - Quick connect box FC Power 5G2.5 branching 3 pole, code 1 (L2)

#### Product accessories



Stecker\_01\_03 - Connexions enfichable Code 1 pour tension de réseau, 3 pôles null





48100/L2/3C1/S - Quick connect box FC Power 5G2.5 branching 3 pole, code 1 (L2)

### Product systems

Flat cable system Power 5G2.5 mm <sup>2</sup> This system is used in offices, supermarkets, shopping malls, exhibitions, industry and for lighting installations in parking garages, train stations or temporary installations. The numerous connections can be removed, attached or moved very easily	
Quick Connect Box 48100 Power Series Quick Junction Boxes Series 48100 for flat cable Power 5G2.5mm <sup>2</sup> The screwless quick junction box allows an even easier and safer installation compared to existing connection systems. A tool-less assembly (assembly errors due to cable geometry impossible), connection longitudinal, use even in narrow ducts, time required for installation less than 1 minute, integrated mounting for ceiling or wall installations.	