



52474/22 - AI lid with rim BOK 22 8880/400 KMn



made of aluminum 3mm dimension: 500x399x26mm edge height inside occupiable: 23mm cable trough loosely enclosed

Characteristics	
Base Unit	Piece
availability	Delivery according to agreement
EAN Code	7611718260360
group	282000
Packaging unit	1
country of origin	СН
Customs tariff number	7616.1090
Weight (g)	1,96 g
Technical data	
Material	PA 6.6
Rated voltage (V)	500 V
Nominal mass	400
Smallest connectable section (mm ²)	0,5 mm²
Stripping length mm (mm)	12 mm
Rating data according to UL 1059	





52474/22 - AI lid with rim BOK 22 8880/400 KMn

Rated voltage US (V)	300 V
Smallest connectable section (AWG)	22 AWG
Stripping length (inch)	0,47 inch





52474/22 - AI lid with rim BOK 22 8880/400 KMn

Product accessories





52474/22 - Al lid with rim BOK 22 8880/400 KMn

Product systems

Floor channel BOK 8880 400x50mm on leveling device Floor channel BOK 8880 400x50mm on leveling device.	
Floor channel BOK 8880 400x60mm on leveling device Floor channel BOK 8880 400x60mm on leveling device.	
Floor channel BOK 8880 400x80mm on leveling device Floor channel BOK 8880 400x80mm on leveling device.	
Floor channel BOK 8880 400x80mm integrated leveling device Floor channel BOK 8880 400x80mm with integrated leveling device.	
Floor channel BOK 8880 400x60mm integrated leveling device Floor channel BOK 8880 400x60mm with integrated leveling device.	
Floor channel BOK 8880 400x50mm integrated leveling device Floor channel BOK 8880 400x50mm with integrated leveling device.	