





















System overview

Flat cable system IP 3G2.5 mm² and 3G4 mm² (IP66/68)



This system is used in tunnelling, civil engineering, industrial plants, workshops and joineries, as well as outdoors for events and open airs, due to its high IP protection level and extraordinary flexibility in terms of changeability and expandability.














Components

	49686 - Flat cable 3G2.5mm² HF GY 2.0 Flat cable Woertz 3x2.5mm 2FR/LS0H light grey LNPE	
	49686/SM - Flat cable 3G2.5mm² HF GY 2.0 Flat cable Woertz 3x2.5mm 2 FR/LS0H light grey+black strip LNPE	
	49686RT - Flat cable 3G2.5mm² HF RD 2.0 Flat cable Woertz 3x2.5mm 2 FR/LS0H red LNPE	
	49685 - Flat cable 3G2.5mm² PVC oil proof GY Flat cable Woertz 3x2.5mm 2PVC(oil resistant) light grey LNPE	
	49685/SM - Flat cable 3G2.5mm² PVC oil proof GY Flat cable Woertz 3x2.5mm 2 PVC(oil resistant) light grey+black stripLNPE	
	49646 - Flat cable 3G4mm² HF GY 2.0 Flat cable Woertz 3x4mm 2 FR/LS0H light grey LNPE	
	48243/L/68 - Junction box FC IP 3G2.5 / 4mm² IP68 3P null	
	48243/SI - Branching box FC IP 3G2.5 / 4mm² IP68 FUSE M20 Branching box with fuse adapter IP66/68 for flat cable WOERTZ IP 3G2.5mm ² and 3G4.0mm ² with 3 cable glands M20x1.5Ø6.0 -15.0mm	
	48243/ST - Branching box FC IP 3G2.5 / 4mm² IP68 Plug Branching box with plug adapter IP66/68 for flat cable WOERTZ IP 3G2.5mm ² and 3G4.0mm ² with 3 cable glands M20x1.5Ø6.0 -15.0mm	



System overview

Flat cable system IP 3G2.5 mm² and 3G4 mm² (IP66/68)

	<p>48243/LED/230V - LED box FC IP 3G2.5 / 4mm² IP68 230V</p> <p>Quick connection technique without tool, light source (light emittingdiode) LED, colour of light white, LED protected against reversepolarity, IP68</p>	
	<p>48510/03 - End piece FC 3G2.5 / 4mm² IP68</p> <p>3G4</p>	
	<p>49935 - Cutting shears up to 6 mm²</p> <p>Woertz flat cable shears up to 5x6 mm² (with higher force up to 5x16 mm²)</p>	
	<p>49385 - Riser clamp</p> <p>Max. Bride load: 50kg. For flat cable: Woertz data 2x1.5 mm², Woertz multibus 4x1.5 mm², Woertz 3G2.5 and 4 mm²</p>	
	<p>49693 - Cable clamp to FK 3G2.5/4 mm²</p> <p>to screw on</p>	
	<p>49462 - Fastening clamp FC 3G2.5 / 4mm² V4A</p> <p>Cable clamp for screwing on</p>	
	<p>49960 - Insulating pad for flat cable</p> <p>Scotch 2210</p>	